

**Features**

- Average cycle time of less than 2 seconds
- High capacity, magazine fed fasteners
- Robust and durable construction
- Lightweight construction and low actuation recoil
- Available with in-line handle or bottom hose configuration
- Low maintenance handtool
- Long life, self priming intensifier
- Long reach barrel

**Benefits**

- Increased productivity
- Reduced component handling and subsequent spillage
- Reduced operator fatigue
- Optimised ergonomic performance for improved productivity
- Productive time is maximised
- Consistent actuation and hence joint formation
- Can be used in many difficult access applications

**Specifications**

Weight (pistol only)	2.6 lbs (1.2 kg)
Pull Force @ 5.5 bar	875 lbf (3.89 kN)
Stroke min.	1.18 ins (30 mm)
Cycle Time	1.0 sec
Air Supply Pressure	5 – 7 bar
Free Air Volume @ 5.1 bar	2.6 litres
Noise Level	< 70 dB(A)
Vibration	< 2.5 m/s <sup>2</sup>
Intensification ratio	32:1

**Placing Capability**

The 7530 placing tool can place the whole range of Speed Fastening® fasteners from diameter 3/32" (2.4 mm) to 1/4" (6.4 mm).

For detailed information on placing capability and nose equipment please refer to the tool manual or contact your local STANLEY Engineered Fastening representative.



**Dimensions (mm/inches)**

